
Exercise 5 - Rating Curve Development

- Develop and plot on the attached logarithmic graph paper a theoretical rating for the channel shown below. You will have to fill out five additional rows in the three data tables that follow. These rows are indicated by arrows.
- In working this problem, you should assume that the sand bar forms a section control. Also, assume that the weir equation applies for the sand bar and that Manning's equation applies for the rest of the channel. When channel control is in effect, the sand bar will be either drowned out or will be washed out.
- The weir equation is used to compute values for a section control, which is represented by the sand bar. Manning's equation should be used to compute data when flow is under channel control. Remember, this is a reach feature, not a single feature at one cross section. The area and wetted perimeter of the sand bar should be disregarded when using Manning's equation.
- Drawing the rating curve will consist of three separate but overlapping curves represented by the green, blue, and red values in the tables below. These are data for the section, channel, and overbank controls respectively. The lines resulting from these separate rating segments should be joined by smooth transitions to form a single rating.

Weir equation: Q = CLH ^{3/2} where C = 2.5, L = Top width, in feet H = Average depth of flow, in feet	Manning equation: $Q = \underbrace{1.486}_{n} AR^{2/3} S^{1/2}$ where: $n = \text{roughness coefficient}$ $A = \text{cross sectional area}$ $R = \text{Hydraulic Radius (A / WP)}$ $S = \text{Energy slope (assume to be same as water surface slope)}$ $(= 0.0009)$
--	--

Schematic diagram of channel



A. Use the weir equation to complete the table below:

GH	L	Ave. H	Q	
1	0	0	0	
1.5	10	0.25	3.12	
2	20	0.5	17.7	
2.5 →				
3 →				
4	40	2	283	
5	40	3	520	
6	40	4	800	

B. Now use Manning's equation to complete this table:

G.H.	Main Channel			Overbank channel					
	Α	WP	R 2/3	Q(main)	Α	WP	R 2/3	Q(over)	Q(Total)
3	80	44	1.49	133					133
4	120	46	1.9	253				-	253
5 →								-	
6	200	50	2.52	562					562
7	240	52	2.77	742					742
8	280	54	3	935				-	935
9	320	56	3.2	1140					1140
11	400	58	3.62	1620	960	962	1.00	530	2150
12 →									
14 →									
16	600	58	4.75	3180	5760	972	3.27	10500	13700
18	680	58	5.16	3910	7680	976	3.96	16900	20800
20	760	58	5.56	4710	9600	980	4.58	24500	29200

C. Use the paper on the next page and the data in the tables above to plot the rating using an appropriate offset.

